


SPECIFICATIONS

PROTECT 200



Protected by
NanoStrike™
technology



MODEL PROTECT 200 (NV200)

Wall mountable or countertop unit, 1-NanoStrike™ coil, supplied with 1.6 m (5.25 ft) power cord (minimum length).

CONSTRUCTION + COLOUR

Precision-cut fabricated metal casing in a white anti-bacterial powder coat finish.

DIMENSIONS

283 mm (h) × 132 mm (w) × 108 mm (d)
11.1" (h) × 5.2" (w) × 4.3" (d)

WEIGHT

3.4 kg | 7.5 lbs

ELECTRICAL RATING

Single Phase, 220-240 VAC | 100-130 VAC, 50-60 Hz
Fuse Rated at 250 VAC, 3 A, Listed

POWER CONSUMPTION RANGE*

220-240 VAC model:

12.7 W – 18.3 W

100-130 VAC model:

12.9 W – 21.8 W

ELECTRICAL CONNECTION

Switched and fused with a grounded, molded power cord.

OPERATING CONDITIONS

10-35 °C | 50-95 °F, 10-75% Relative Humidity

SHIPPING / STORAGE CONDITIONS

5-50 °C | 41-122 °F, <95% Relative Humidity

FAN AIR FLOW VOLUME

80 m³/hr | 47 CFM

NOISE LEVEL*

35 dB

QUALITY & SAFETY

Manufactured under ISO 9001, ISO 14001 & ISO 45001

REGULATORY

IEC 60601-1 & 60601-1-2

IEC 60335-1 & IEC 60335-2-65

CE | Conforms to Low Voltage Directive (LVD)

2014/35/EU

UL 867 | CSA C22.2 NO. 187:20

CARB

FCC

China Disinfection WS/T 648

South Korea KCC

* Power consumption depends on voltage and frequency of network in particular county.

* Measured at the unit.